

ARDON[®]ULTRITE AG

SAFETY GLASSES







© ARDON s.r.o. / ALL RIGHTS RESERVED ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz



ARDON[®]ULTRITE AG

SAFETY GLASSES

ARTICLE NO. E4302

Lens materiál Material frame Temple material Lens Polycarbonate Grilamid TR Grilamid TR gold REVO



DESCRIPTION

Soft ribbed nose bridge, rubberized, non-slip, and softened temple tips. The double luxury Gold REVO antireflective coating offers perfect, sharp, and clear vision with top optical performance. Above-standard surface treatment against abrasion and fogging (NK certification), UV protection up to 400 nm. The frame of these glasses is made from Grilamid TR 11261 natural material, which contains 51% carbon from renewable sources. Grilamid TR is lighter than polycarbonate, yet stronger and more durable, while also providing high resistance to chemicals and high temperatures.

Applications: outdoor work, construction sites, driving, roadwork, sports activities

© ARDON s.r.o. / ALL RIGHTS RESERVED ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz



STANDARDS

This personal protective equipment complies with the requirements of the following harmonized standard:

EN ISO 16321-1:2022:	Eye and face protection for occupational use
EN 166:2001:	Personal eye protection equipment - Basic requirements

The safety glasses meet the requirements of Regulation (EU) 2016/425 of the European Parliament and of the Council on personal protective equipment and Regulation (EU) 2023/998 of the European Parliament and of the Council on general product safety.

Certification was carried out based on the product's technical documentation and practical testing of ergonomic properties by Ardon s.r.o. on June 11, 2025. Final manufacturer's report no. TR 250610004.



Lens gold REVO, UV 400, AR GL3 CT KN

Filtre type	GL	UV filter
Shade number		gold
Optical class	1	Permanent wear
Mechanical resistance	СТ	Resistence to low-energy particle impacts at extreme temperatures
Anti-fog lens	\checkmark	\bigcirc
Scratch resistant coating	\checkmark	
UV protective coating	1	UV400

© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz



NUMBER OF PIECES IN CARTON300 pcQUANTITY PER BOX10 pcCARTON WEIGHT21,5 kgCARTON SIZE0,18 m³UNIT PACKAGING1 pc



The product must be stored in its packaging in a dry, clean place, away from direct sunlight, at temperatures between +5°C and +55°C, with relative humidity up to 90%, and away from sources of gasoline or solvent vapors.

Cleaning is recommended after each use. Clean at room temperature using a soft cloth lightly moistened with a diluted solution of water and mild detergent.

Do not use hot water, gasoline, degreasers, organic solvents, or abrasive cleaning agents.

© ARDON.s.r.o. / ALL RIGHTS RESERVED ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz





© ARDON s.r.o. / ALL RIGHTS RESERVED ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz