

# **ARDON®ULTRITE LG**

SAFETY GLASSES















## **ARDON®ULTRITE LG**

SAFETY GLASSES

ARTICLE NO. E4303

Lens materiál Polycarbonate

Material frame Grilamid TR

Temple material Grilamid TR

Lens gold REVO



#### **DESCRIPTION**

Soft ribbed nose bridge, rubberized, non-slip, and softened temple tips. The double luxury Gold REVO antireflective coating with a reddish tint provides perfect, sharp, and clear vision along with top-notch optical performance. Premium surface treatment resists scratches and fogging (NK certified) and offers UV protection up to 400 nm. The frame of these glasses is made from Grilamid TR 11261 natural, a material that contains 51% carbon from renewable sources. Grilamid TR is lighter than polycarbonate, yet stronger and more durable, while also offering high resistance to chemicals and elevated temperatures.

Applications: outdoor work, construction sites, driving, roadwork, sports activities



### **STANDARDS**

This personal protective equipment complies with the requirements of the following harmonized standard:

EN ISO 16321-1:2022: Eye and face protection for occupational use

EN 166:2001: Personal yey protection equipment - Basic requirementrs

The safety glasses meet the requirements of Regulation (EU) 2016/425 of the European Parliament and of the Council on personal protective equipment and Regulation (EU) 2023/998 of the European Parliament and of the Council on general product safety. Certification was carried out based on the product's technical documentation and practical testing of ergonomic properties by Ardon s.r.o. on June 11, 2025. Final manufacturer's report no. TR 05061003.

### Lens blue REVO, UV 400, AR GL3 CT KN

Filtre type	GL	UV filter
Shade number	3	gold
Optical class	1	Permanent wear
Mechanical resistance	СТ	Resistence to low-energy particle impacts at extreme temperatures
Anti-fog lens	✓	
Scratch resistant coating	✓	Fam
UV protective coating	✓	UV400





NUMBER OF PIECES IN CARTON
QUANTITY PER BOX
10 pc
CARTON WEIGHT
21,5 kg
CARTON SIZE
0,18 m³
UNIT PACKAGING
1 pc

The product must be stored in its packaging in a dry, clean place, away from direct sunlight, at temperatures between +5°C and +55°C, with relative humidity up to 90%, and away from sources of gasoline or solvent vapors.

Cleaning is recommended after each use. Clean at room temperature using a soft cloth lightly moistened with a diluted solution of water and mild detergent.

**Do not use** hot water, gasoline, degreasers, organic solvents, or abrasive cleaning agents.





